

Trust In Quality, Count On Warmth.

For over 45 years, DS Stoves has been committed to providing exceptional heating and cooking solutions. Each product showcases traditional craftsmanship. thoughtfully designed for optimal efficiency and low maintenance. Built by master craftsman in Lancaster County, Pennsylvania, DS products are synonymous with superior quality, dependable performance, and lasting value—guaranteed to provide warmth and reliability for a lifetime.

| Which D5 |
|----------------|
| product is |
| right for you? |

| right for you? | First | Basen | Whole | Force | Anthr | Mond | Gas | Free | Hot IA | Green | - |
|---------------------------------|-------|-------|-------|-------|-------|------|-----|------|--------|-------|---|
| Anthra-Max | • | • | • | | • | | | • | | | |
| Anthra-Max Fireplace Insert | • | • | • | | • | | | | | | |
| Anthra-Glo | • | • | • | | • | | | • | | | |
| Aqua-Gem | | • | • | | • | | | • | • | • | |
| Aqua-Stoke | | • | • | | • | | | • | • | • | |
| Comfort Max | • | • | • | | • | | | • | | | |
| Dawn Series | • | | • | | | | • | • | | | |
| Dawn Series Fireplace Insert | • | | • | | | | • | | | | |
| Ecomiser | | • | • | • | • | | | • | | • | |
| EnergyMax #ND110 | • | • | • | | • | | | • | | | |
| EnergyMax #ND160 | | • | • | | • | | | • | | • | |
| Gas Boiler | | • | • | | | | • | • | • | • | |
| Gas Furnace | | • | • | | | | • | • | | • | |
| GH Blast | | | | | • | • | | • | | • | |
| HeatRight | | • | • | | • | | | • | | | |
| Heco Elite Series | • | | • | | • | • | | • | | | |
| Heco InLine Series | • | | • | | | • | | • | | | |
| Homeland Series | • | | • | | | • | | • | | | |
| Kozy-King | | • | • | • | • | | | • | | • | |
| Power Boilers | | | | | • | • | | • | • | • | |
| Stoker Furnace | | • | • | • | • | | | • | • | • | |

Things To Consider When Purchasing

| Anthra-Max #XV14 |
|---|
| Anthra-Max #XV15 |
| Anthra-Max #XV16 |
| Living Room Style Sheet Metal |
| Basement Style Sheet Metal |
| Front Loading Baffle |
| Blower Kit |
| Cover Lid |
| Step Top w/ Cover Lid |
| Warming Shelf |
| CO & Smoke Alarm |
| 00 d 0110k0/lid111 |
| Stovepipeftin. |
| Black □ Stainless Steel □ |
| Filhaura (O May) |
| Elbows (2 Max)Pieces |
| Black □ Stainless Steel □ |
| Insulated Chimneyft. |
| Masonry Stainless Steel |
| |
| Hearth Board |
| (Size / Model) |
| Moll Protection Board |
| Wall Protection Board |
| (Size / Model) |
| Subtotal |
| |
| Tax |
| DS2025 Prices are subject to change without notification Total |

Authorized Dealer



Anthra-Max

Models #XV14, #XV15, #XV16



Where Tradition, Craftsmanship, and Quality Come First

THE DS HOT AIR CIRCULATOR SYSTEM



Vertical tubes in the firebox increase the heating surface area by approximately 50%. Heat rises inside the tubes, drawing cooler air from the floor. This convection process produces circulation with no need for electrical blowers or fans, meaning even heat throughout your home.

DS HOT AIR DRAFT REGULATOR

The DS Regulator is not electrical. It uses two different metals bonded together. The metals expand and contract based on temperature, directing the heat to where it is needed. Mounted directly on the hot surface of the stove, it governs the temperature by opening or closing the draft control. This draft control connects to a specially designed draft intake through which air can enter to increase or decrease the temperature of the fire. The DS Regulator is equipped with a 5-position mechanical control dial.





Efficiency & Practicality

Efficiency and function is the focus of the Anthra-Max. Designed for the first floor or basement, the Anthra-Max is more than a great looking stove, it will heat your entire home without breaking a sweat!

FEATURES

- Burns Anthracite
- DS Hot Air Draft Regulator
- Reburn Baffle System
- Gravity Fed Hopper
- Front Loading Option
- Large Glass View w/ Airwash
- Airtight Cast Iron Doors
- Heat Exchanger Tubes To Maximize Efficiency
- Superior Cast Iron Shaker Grates
- Dust-Free Exterior Shaker Handle
- Removable Firebrick Retainers
- Gravity Fed Hopper
- Extra Wide Ash Pan
- Constructed From Heavy Plate Steel
- Manufactured In Lancaster County, PA



XV14 Shown w/ Living Room Style Sheet Metal & Optional Top Cover Lid

Also shown is the reburn baffle system in action. Gases from anthracite are being burned off creating a cleaner burn, more heat, less ash, and less clinkers. The reburn effect will not look like this most of the time.

SPECIFICATIONS

| Model Number | XV14 | XV15 | XV16 |
|--------------------------------|-----------------------|-----------------------|-----------------------|
| Fuel | Anthracite | Anthracite | Anthracite |
| Heating Area (Recommended) | 500 - 1,400 sq. ft. | 1,000 - 2,000 sq. ft. | 1,500 - 2,500 sq. ft. |
| BTU (Approx) | 55,000 | 72,000 | 105,000 |
| Efficiency | 82.8% | 82.8% | 82.8% |
| Fire Box (WxDxH) | 16" x 12" x 14" | 16" x 16" x 14" | 16" x 20" 14" |
| Fire Box Height To Hopper | 11.5" | 11.5" | 11.5" |
| Fire Box Volume | 1.55 cu. ft. | 2.0 cu. ft. | 2.60 cu. ft. |
| Fire Door (WxH) | 18.25" x 11.75" | 18.25" x 11.75" | 18.25" x 11.75" |
| Ash Pan (WxDxH) | 18" x 12" x 3.5" | 18" x 16" x 3.5" | 18" x 20" x 3.5" |
| Ash Door (WxH) | 19" x 5.25" | 19" x 5.25" | 19" x 5.25" |
| Hopper Capacity | 40 lbs. | 40 lbs. | 40 lbs. |
| Total Capacity w/ Hopper | 85 lbs. | 110 lbs. | 130 lbs. |
| Hopper Door (WxD) | 11.75" x 8.5" | 11.75" x 8.5" | 11.75" x 8.5" |
| Rear Exhaust | 6" (32.25" To Center) | 6" (32.25" To Center) | 6" (32.25" To Center) |
| Optional Blower Max CFM | 125 | 125 | 125 |
| Optional Top Cover Lid | Available | Available | Available |
| Optional Step Top | N/A | Available | Available |
| Size w/ Living Room SM (WxDxH) | 28.5" x 22.5" x 39.5" | 28.5" x 26.5" x 39.5" | 28.5" x 31.5" x 39.5" |
| Size w/ Basement SM (WxDxH) | N/A | 34.5" x 26.5" x 39.5" | 34.5" x 31.5" x 39.5" |
| Weight | 490 lbs. | 590 lbs. | 650 lbs. |
| U.L. Tested* | Yes | Yes | Yes |
| Warranty | 5 Year Limited | 5 Year Limited | 5 Year Limited |

CLEARANCE FROM COMBUSTIBLES

| OLEANANOL I HOM COMBOOTIBLE | | | | | | |
|-----------------------------|-----|-----|-----|--|--|--|
| Front | 48" | 48" | 48" | | | |
| Back | 18" | 18" | 18" | | | |
| Sides | 18" | 18" | 18" | | | |
| Corner | 9" | 9" | 9" | | | |
| Ceiling | 36" | 36" | 36" | | | |
| Flue / Stovepipe | 18" | 18" | 18" | | | |



XV15 Shown w/ Living Room Style Sheet Metal & Optional Step Top



XV16 Shown w/ Basement Style Sheet Metal

All units require a Class "A" all fuel chimney. Installation must conform to state and local codes. * Safety Tested to UL #1482, UL #391, ETLM 78-1 and CAN / CSA B-366.1