

To strive to make the most competitive and highest quality products available. Traditional craftsmanship defines each product from wood and anthracite cookstoves to custom metal fabrication. With a goal of high efficiency and low maintenance, DS products are built to last a lifetime. With four divisions, Stove Manufacturing, Retail, Wholesale, and Custom Fabrication, DS strives for excellence in everything they produce.

Which D5 product is right for you?	First E.	Baser	Whole is	Forces is	Anthra Hot Air	Wood	Gas	French	Hot West	Greenhe Heating	dous / Shop
Anthra-Max	•	•	•		•			•			
Anthra-Max Fireplace Insert	•	•	•		•						
Anthra-Glo	•	•	•		•			•			
Aqua-Gem Boilers #1100, 3200, 4200		•	•		•				•	•	
Aqua-Stoke		•	•		•				•	•	
Comfort Max	•	•	•		•			•			
Ecomiser		•	•	•	•					•	
EnergyMax #110	•	•	•		•			•			
EnergyMax #160		•	•		•			•		•	
Gas Boiler		•	•				•		•	•	
Gas Furnace		•	•				•			•	
GH Blast					•	•		•		•	
HeatRight		•	•		•			•			
HECO Cookstove	•		•		•	•		•			
Kozy-King		•	•	•	•					•	
Power Boilers #5000, 6000, 7000					•	•			•	•	
Stoker Furnace		•	•	•	•				•	•	

Things To Consider When Purchasing

DS2023		
Aqua-Gem #4200	Aqua-Gem #1100	
Insulated Jacket Kit	Aqua-Gem #3200	
Domestic Water Coil	Aqua-Gem #4200	
Domestic Water Coil	Insulated Jacket Kit	
Aquastat (L6006A)		
Feed Water Regulator (EB-75)		
Expansion Tank		
Forced Draft Kit (FDK-002A)	Expansion Tank	
Mixing Valve		
Mixing Valve	Circulator Pump	
1/8" NPT Auto Air Vent		
Optional Rear Exhaust		
Stovepipeftin. Black □ Stainless Steel □		
Stovepipeftin. Black □ Stainless Steel □	CO & Smoke Alarm	
Black Stainless Steel Elbows (2 Max)Pieces Black Stainless Steel Screws For Stovepipe Black Stainless Steel Damper Manual Barometric Insulated Chimneyft. Masonry Stainless Steel Subtotal Tax		
Elbows (2 Max)Pieces Black □ Stainless Steel □		
Screws For Stovepipe Black Stainless Steel Damper Manual Barometric Insulated Chimney Insulated Chimney Stainless Steel Subtotal Tax Insulated Insulated		
Black Stainless Steel Damper Manual Barometric Insulated Chimney Stainless Steel Subtotal Tax	Black □ Stainless Steel □	
Damper Manual Barometric Insulated Chimney Stainless Steel Subtotal Tax Tax	Screws For Stovepipe	
Manual Barometric Insulated Chimney Insulated Chimney Stainless Steel Subtotal Tax	Black □ Stainless Steel □	
Insulated Chimneyft. Masonry Stainless Steel Subtotal Tax	Damper	
Masonry Stainless Steel Subtotal Tax Tax	Manual □ Barometric □	
Subtotal Tax	Insulated Chimneyft.	
ns2023	Masonry □ Stainless Steel □	
DS2023	Sub	total
DS2023	200000	Tax
These are subject to sharige without notineation	DS2023 Prices are subject to change without notification	Total

Authorized Dealer



Aqua-Gem

Models #1100, #3200, #4200



Comfort Throughout Your Space

This hydronic system requires no electricity to heat water for floor heating, baseboard, freestanding radiators, heat pumps, or domestic water. They work well with new or existing oil or electric boilers. Our boilers circulate water in the front to prevent cracking. Each unit is pressure tested to 120 PSI and has a powerful heat exchanger for maximum efficiency. Constructed from 1/4" steel, the Aqua-Gem boilers easily maintain water temperature and feature a large capacity ash pan. All of our boilers are designed with a superior cast iron grate system and built to last.



#3200 Shown With Insulated Jacket Kit

FEATURES

- Burns Anthracite
- Safety Tested To U.L. Standards
- Reburn System
- Airtight Cast Iron Doors
- Heavy Duty Cast Iron Grate System w/ External Shaker Handle
- 1/2" NPT Fitting For Temperature Pressure Gauge
- 3/4" NPT Fitting For Aquastat
- 3/4" Fitting For Hot Water Draft Regulator
- Large 6" High Ash Pan
- Optional 4 or 5 Gallon Per Minute Domestic Water Coil
- Optional Forced Draft
- Optional Insulated Jacket
- Manufactured In Lancaster County, PA



The optional 4 or 5 gallon per minute domestic water coil can heat your hot water or work in conjunction with your existing domestic water system saving money over gas, electric, or fuel oil.

SPECIFICATIONS

Model Number	1100	3200	4200
Fuel	Anthracite	Anthracite	Anthracite
Heating Area (Recommended)	1,000 - 2,400 sq. ft.	2,000 - 3,500 sq. ft.	3,000 - 5,000 sq. ft.
BTU (Approx)	100,000	160,000	230,000
Efficiency	78%	78%	78%
Firebox (WxDxH)	16.5" x 19" x 20"	19" x 24" x 25"	19" x 30" x 25"
Firebox Volume	3.6 cu. ft.	6.6 cu. ft.	8.2 cu. ft.
Fire Door (WxH)	11" x 12"	14" x 14.5"	14" x 14.5"
Ash Pan (WxDxH)	15" x 18" x 6"	15.5" x 22" x 6"	15.5" x 28" x 6"
Ash Door (WxH)	16.5" x 9"	16.5" x 9"	16.5" x 9"
Top Exhaust (Standard)	6"	7"	8"
Rear Exhaust (Optional)	6" (39" To Center)	7" (42.5" To Center)	8" (42.5" To Center)
Water Capacity	27 Gallons	40 Gallons	45 Gallons
Inlet / Outlet	4 (1.25")	4 (2.00")	4 (2.00")
Overall Size (WxDxH)	23.5" x 25" x 49.5"	26" x 30" x 53.5"	26" x 36" x 53.5"
Weight	800 lbs.	1,050 lbs.	1,250 lbs.
U.L. Tested*	Yes	Yes	Yes
Insulated Jacket	Optional	Optional	Optional
Warranty	5 Year Limited 1 Year Controls	5 Year Limited 1 Year Controls	5 Year Limited 1 Year Controls

CLEARANCE FROM COMBUSTIBLES

•	OLLAHANOL I HOW COMBOSTIBLES							
1	Front	48"	48"	48"				
ı	Back	16"	16"	16"				
;	Sides	12"	12"	12"				
(Ceiling	36"	36"	36"				
ı	Flue / Stovepipe	18"	18"	18"				

^{*} Safety Tested to U.L. 391, ETLM78-1, CAN/CSA B366.1

All units require a Class "A" all fuel chimney. Installation must conform to state and local codes.