

Trust In Quality, Count On Warmth.

For over 45 years, DS Stoves has been committed to providing exceptional heating and cooking solutions. Each product showcases traditional craftsmanship, thoughtfully designed for optimal efficiency and low maintenance. Built by master craftsman in Lancaster County, Pennsylvania, DS products are synonymous with superior quality, dependable performance, and lasting value—guaranteed to provide warmth and reliability for a lifetime.

Which ID:5 product is right for you?	First	Basem	Whole is	Forced :	Anthro Hot Air	Wood	Gas	French	Hot Med Unit	Greenhe Heating	Shon Shon
Anthra-Max	•	•	•		•			•			
Anthra-Max Fireplace Insert	•	•	•		•						
Anthra-Glo	•	•	•		•			•			
Aqua-Gem		•	•		•			•	•	•	
Aqua-Stoke		•	•		•			•	•	•	
Comfort Max	•	•	•		•			•			
Dawn Series	•		•				•	•			
Dawn Series Fireplace Insert	•		•				•				
Ecomiser		•	•	•	•			•		•	
EnergyMax #ND110	•	•	•		•			•			
EnergyMax #ND160		•	•		•			•		•	
Gas Boiler		•	•				•	•	•	•	
Gas Furnace		•	•				•	•		•	
GH Blast					•	•		•		•	
HeatRight		•	•		•			•			
Heco Elite Series	•		•		•	•		•			
Heco InLine Series	•		•			•		•			
Homeland Series	•		•			•		•			
Kozy-King		•	•	•	•			•		•	
Power Boilers					•	•		•	•	•	
Stoker Furnace		•	•	•	•			•	•	•	

Things To Consider When Purchasing

Aqua-Gem #1100
Aqua-Gem #3200
Aqua-Gem #4200
Insulated Jacket Kit
Domestic Water Coil
Aquastat (L6006A)
Feed Water Regulator (EB-75)
Expansion Tank
Forced Draft Kit (FDK-002A)
Circulator Pump
Mixing Valve
1/8" NPT Auto Air Vent
Optional Rear Exhaust
CO & Smoke Alarm
Stovepipeftin.
Black □ Stainless Steel □
Elbows (2 Max)Pieces
Black □ Stainless Steel □
Screws For Stovepipe
Black □ Stainless Steel □
Damper
Manual □ Barometric □
Insulated Chimneyft.
Masonry □ Stainless Steel □
Subtotal
DS2025
Prices are subject to change without notification Total

Authorized Dealer



Aqua-Gem

Models #1100, #3200, #4200



Comfort Throughout Your Space

This hydronic system requires no electricity to heat water for floor heating, baseboard, freestanding radiators, heat pumps, or domestic water. They work well with new or existing oil or electric boilers. Our boilers circulate water in the front to prevent cracking. Each unit is pressure tested to 120 PSI and has a powerful heat exchanger for maximum efficiency. Constructed from 1/4" steel, the Aqua-Gem boilers easily maintain water temperature and feature a large capacity ash pan. All of our boilers are designed with a superior cast iron grate system and built to last.



#3200 Shown With Insulated Jacket Kit

FEATURES

- Burns Anthracite
- Safety Tested To U.L. Standards
- Reburn System
- Airtight Cast Iron Doors
- Heavy Duty Cast Iron Grate System w/ External Shaker Handle
- 1/2" NPT Fitting For Temperature Pressure Gauge
- 3/4" NPT Fitting For Aguastat
- 3/4" Fitting For Hot Water Draft Regulator
- Large 6" High Ash Pan
- Optional 4 or 5 Gallon Per Minute Domestic Water Coil
- Optional Forced Draft
- Optional Insulated Jacket
- Manufactured In Lancaster County, PA



The optional 4 or 5 gallon per minute domestic water coil can heat your hot water or work in conjunction with your existing domestic water system saving money over gas, electric, or fuel oil.

SPECIFICATIONS

Model Number	1100	3200	4200
Fuel	Anthracite	Anthracite	Anthracite
Heating Area (Recommended)	1,000 - 2,400 sq. ft.	2,000 - 3,500 sq. ft.	3,000 - 5,000 sq. ft.
BTU (Approx)	100,000	160,000	230,000
Efficiency	78%	78%	78%
Firebox (WxDxH)	16.5" x 19" x 20"	19" x 24" x 25"	19" x 30" x 25"
Firebox Volume	3.6 cu. ft.	6.6 cu. ft.	8.2 cu. ft.
Fire Door (WxH)	11" x 12"	14" x 14.5"	14" x 14.5"
Ash Pan (WxDxH)	15" x 18" x 6"	15.5" x 22" x 6"	15.5" x 28" x 6"
Ash Door (WxH)	16.5" x 9"	16.5" x 9"	16.5" x 9"
Top Exhaust (Standard)	6"	7"	8"
Rear Exhaust (Optional)	6" (39" To Center)	7" (42.5" To Center)	8" (42.5" To Center)
Water Capacity	27 Gallons	40 Gallons	45 Gallons
Inlet / Outlet	4 (1.25")	4 (2.00")	4 (2.00")
Overall Size (WxDxH)	23.5" x 25" x 49.5"	26" x 30" x 53.5"	26" x 36" x 53.5"
Weight	800 lbs.	1,050 lbs.	1,250 lbs.
U.L. Tested*	Yes	Yes	Yes
Insulated Jacket	Optional	Optional	Optional
Warranty	5 Year Limited 1 Year Controls	5 Year Limited 1 Year Controls	5 Year Limited 1 Year Controls

CLEARANCE FROM COMBUSTIBLES

OLLAHANOL I HOM OUMDOSTIDELS						
Front	48"	48"	48"			
Back	16"	16"	16"			
Sides	12"	12"	12"			
Ceiling	36"	36"	36"			
Flue / Stovepipe	18"	18"	18"			

^{*} Safety Tested to U.L. 391, ETLM78-1, CAN/CSA B366.1

All units require a Class "A" all fuel chimney. Installation must conform to state and local codes.