

To strive to make the most competitive and highest quality products available. Traditional craftsmanship defines each product from wood and anthracite cookstoves to custom metal fabrication. With a goal of high efficiency and low maintenance, DS products are built to last a lifetime. With four divisions, Stove Manufacturing, Retail, Wholesale, and Custom Fabrication, DS strives for excellence in everything they produce.

Which D5 product is right for you?	First E.	Basar	Whole !:	Forces	Anthro Hot Air	Wood	la se	French	Hot Wei	Greenh	Shop
Anthra-Max	•	•	•		•			•			
Anthra-Max Fireplace Insert	•	•	•		•						
Anthra-Glo	•	•	•		•			•			
Aqua-Gem Boilers #1100, 3200, 4200		•	•		•				•	•	
Aqua-Stoke		•	•		•				•	•	
Comfort Max	•	•	•		•			•			
Ecomiser		•	•	•	•					•	
EnergyMax #110	•	•	•		•			•			
EnergyMax #160		•	•		•			•		•	
Gas Boiler		•	•				•		•	•	
Gas Furnace		•	•				•			•	
GH Blast					•	•		•		•	
HeatRight		•	•		•			•			
HECO Cookstove	•		•		•	•		•			
Kozy-King		•	•	•	•					•	
Power Boilers #5000, 6000, 7000					•	•			•	•	
Stoker Furnace		•	•	•	•				•	•	

Things To Consider When Purchasing
CoalMaster
CO & Smoke Alarm
Stovepipeftin. Black □ Stainless Steel □
Elbows (2 Max)Pieces Black Stainless Steel
Screws For Stovepipe Black □ Stainless Steel □
Damper Manual □ Barometric □
Insulated Chimneyft.
Masonry □ Stainless Steel □
Hearth Board(Size / Model)
Wall Protection Board(Size / Model)
Subtotal
Tax
Total
DS2023 Prices are subject to change without notification
Authorized Dealer



CoalMaster

Model #2100WH



Stay Warm Longer

The CoalMaster can heat your entire home using no electricity. The gravity-fed hopper provides up to two days of continuous heat. This basement model features Pyroceramic glass in the fire door for monitoring. The CoalMaster Works great in greenhouses and shops too.

FEATURES

- Burns Anthracite
- DS Hot Air Draft Regulator
- 24 48 Hour Burn Time
- Removable Hopper
- Airtight Cast Iron Doors
- Superior Cast Iron Shaker Grates
- Exterior Shaker Handle
- Minimal Dust
- Constructed From Heavy Plate Steel
- Manufactured In Lancaster County, PA

DS HOT AIR DRAFT REGULATOR

The DS Regulator is not electrical. It uses two different metals bonded together. The metals expand and contract based on temperature, directing the heat to where it is needed. Mounted directly on the hot surface of the stove, it governs the temperature by opening or closing the draft control. This draft control connects to a specially designed draft intake through which air can enter to increase or decrease the temperature of the fire. The DS Regulator is equipped with a 5-position mechanical control dial.





SPECIFICATIONS

Model Number	2100WH
Fuel	Anthracite
Heating Area (Recommended)	1,500 - 3,000 sq. ft.
BTU (Approx)	130,000
Efficiency	80%
Fire Box (WxDxH)	16" x 20" x 20.5"
Fire Box Height To Hopper	12.5"
Fire Box Volume	4.0 cu. ft.
Hopper Capacity	50 lbs.
Total Capacity w/ Hopper	135 lbs.
Fire Door (WxH)	16" x 10.5"
Ash Pan (WxDxH)	15.5" x 21" x 3.5"
Ash Door (WxH)	16.5" x 5.5"
Rear Exhaust	6" (33.25" To Center)
Overall Size (WxDxH)	27.75" x 27" x 40"
Weight	540 lbs.
U.L. Tested*	Yes
Warranty	5 Year Limited

CLEARANCE FROM COMBUSTIBLES

Front 48" Back 24" Sides 18" Ceiling 36" Flue / Stovepipe 18"		
Sides 18" Ceiling 36"	Front	48"
Ceiling 36"	Back	24"
•	Sides	18"
Flue / Stovepipe 18"	Ceiling	36"
	Flue / Stovepipe	18"

All units require a Class "A" all fuel chimney.
Installation must conform to state and local codes.
* Safety Tested to U.L. 391, ETLM78-1, CAN/CSA B366.1

